

Specifications MINI Cooper Clubman. (Stand: January 2010)

Body		MINI Cooper Clubman	MINI Cooper Clubman automatik
No of doors/seats		5 / 5 (optional 4 Sitzplätze)	5 / 5 (optional 4 Sitzplätze)
Length/width/height (unladen)	mm	3937 / 1683 / 1426	3937 / 1683 / 1426
Wheelbase	mm	2 547	2 547
Track front/rear	mm	1459 / 1467	1459 / 1467
Turning circle	m	11,0	11,0
Fuel tank capacity	approx. l	40	40
Cooling system including heater	l	5,2	5,2
Engine oil	l	4,2	4,2
Transmission fluid incl final drive	l	permanent filling	permanent filling
Weight, unladen, according to DIN/EU ¹	kg	1145 / 1220	1175 / 1250
Max load according to DIN	kg	500	500
Max permissible weight to DIN	kg	1645	1675
Max permissible axle load front/rear	kg	840 / 840	870 / 850
Max permissible trailer load ²			
braked (12%/unbraked)	kg	750 / 500	750 / 500
Max roof load / max towbar download	kg	75 / 50	75 / 50
Luggage compartment according to DIN	l	260-930	260-930
Air resistance	c _x x A	0,34 x 2,01	0,34 x 2,01
Engine			
Configuration/No of cylinders/valves		Inline / 4/ 4	Inline / 4/ 4
Engine management		MEV 17.2	MEV 17.2
Capacity	cm ³	1598	1598
Bore/stroke	mm	77 / 85,8	77 / 85,8
Compression ratio	:1	11,0	11,0
Fuel	ROZ	91-98	91-98
Max output	kW/PS	90 / 122	90 / 122
at	min ⁻¹	6 000	6 000
Max torque	Nm	160	160
at	min ⁻¹	4 250	4 250
Electrical system			
Battery/installation	Ah/-	46 / vorn	46 / vorn
Alternator	A/W	120 / 1680	120 / 1680
Chassis and suspension			
Front suspension		Single-joint Mc Pherson spring strut axle with anti-dive	
Rear suspension		Longitudinal struts with centrally-pivoted control arms, Z-axle	
Brake, front		Vented disc	Vented disc
Diameter	mm	280	280
Brake, rear		Disc brake	Disc brake
Diameter	mm	259	259
Driving stability systems		Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD), Cornering Brake Control (CBC) and Brake Assistant. Optional: ASC+T traction control, Dynamic Stability Control (DSC) with Hill Start Assistant, Limited-slip differential.	
Steering		Electric power steering (EPS)	
Overall transmission ratio	:1	14,1	14,1
Type of transmission		6-gear-manual	6-gear-automatic
Gear ratios			
I	:1	3,214	4,148
II	:1	1,792	2,370
III	:1	1,194	1,556
IV	:1	0,914	1,155
V	:1	0,784	0,859
VI	:1	0,683	0,686
R	:1	3,143	3,394
Final drive ratio	:1	4,353	4,103
Tyres		175 / 65 R15 84H	175 / 65 R15 84H
Wheels		5.5Jx15 LM	5.5Jx15 LM
Performance			
Power-to-weight ratio, DIN	kg/kW	12,7	13,5
Output per litre	kW/l	56,3	56,3
Acceleration			
0-62 mph	s	9,8	10,9
0-1000 m	s	30,9	32,0
in 4th/5th gear	50-75 mph	10,2 / 12,7	-
Top speed	km/h	201	195
Consumption in the EU cycle			
Urban	l/100 km	7,0	8,8
Extra-urban	l/100 km	4,7	5,2
Combined	l/100 km	5,5	6,5
CO2	g/km	129	152
Miscellaneous			
Emission category	-	EU5	EU5
Insurance ratings Germany	HPF/VK/TK	13 / 17 / 19	13 / 17 / 19
Ground clearance	mm	138	138

¹ Gewicht des betriebsfertigen Fahrzeugs (DIN) plus 75 kg für Fahrer und Gepäck.

² Erhöhungen sind unter bestimmten Voraussetzungen möglich.